

## SIMONA® PE welding rods, round (RD)

---

PE-HWU-B			PE-HWST		
black			natural		
d mm	coils/ spools	sticks m	coils/ spools	sticks m	ca. m/kg
3	C + S <sup>1</sup>	1	C		150
4	C + S <sup>1</sup>	1	C + S		85
5	C		C		45

PE-EL			PE-HML 500		PE 100		
black			natural		black		
d mm	coils/ spools	sticks m	coils/ spools	sticks m	coils/ spools	sticks m	ca. m/kg
3	C		C		S		150
4	C		C		C + S		85
5							45

<sup>1</sup> also in 10 kg

**Tolerance in thickness: max. ± 0.3 mm**

**availability:**

- 1 = 1 m rods in 2 kg bags
- 2 = 2 m rods in 4 kg bags
- Coils appr. 3-4 kg
- Spools appr. 2.5 – 3 kg

**on request:**

- other sizes and diameters
- welding rods from soft PE (PE-LD)

## SIMONA<sup>®</sup> PE welding rods, triangular

---

black

---

### PE-HWU-B (TA 90)

a mm	b mm	coils/ spools	sticks m	ca. m/kg
4	2.8		2	125
5	3.6	R	1 / 2	85
6	4.5	R	2	55
7	5,0		2	30

### PE-HWU-B (TA 80)

a mm	b mm	coils/ spools	sticks m	ca. m/kg
5	3.0	R + S		115
6	3.6	R		80
7	4.3	R		55

**Tolerance in thickness: max.  $\pm$  0.3 mm**

**availability:**

- 1 = 1m rods in 2 kg bags
- 2 = 2m rods in 4 kg bags
- Coils appr. 3-4 kg
- Spools appr. 2.5 – 3 kg

**on request:**

- other sizes and diameters
- welding rods from soft PE (PE-LD)

## SIMONA<sup>®</sup> PE welding rods, three-core (TL)

---

black

---

PE-HWU-B				
a mm	b mm	coils/ spools	sticks m	ca. m/kg
5	3.5	C		90

**Tolerance in thickness: max.  $\pm$  0.3 mm**

**availability:**

- 1 = 1m rods in 2 kg bags
- 2 = 2m rods in 4 kg bags
- Coils appr. 3-4 kg
- Spools appr. 2.5 – 3 kg

**on request:**

- other sizes and diameters
- welding rods from soft PE (PE-LD)